INDUSTRIAL ENCLOSURES

BY TRICEL

40+ YEARS TECHNICAL EXPERIENCE



IP43 DOUBLE DOOR ELECTRICAL ENCLOSURE

750 x 1000 x 300MM

COMPLIES TO IEC 62208:2011

STOCK CODE: **103970**

TRICEL CONSTRUCTION

STOCK CODE:
103970

IP43 DOUBLE DOOR ELECTRICAL ENCLOSURE

750 x 1000 x 300MM

COMPLIES TO IEC 62208:2011

INDUSTRIAL ENCLOSURES BY TRICEL

40+ YEARS TECHNICAL EXPERIENCE



Central divider can be cut or drilled to suit customer requirements.

Door locking mechanism must not be interfered with.



Example: double door electric enclosure

INTERNAL DIMENSIONS & CAPACITY

Dimensions: 721mm high x 428mm wide x 240mm deep

Capacity: 0.074m^3 per section, total capacity 0.148m^3

SPECIFICATION & KEY FEATURES

- Comes complete with a backboard and triple lock system.
- Made from GRP. Compression moulded from fibreglass reinforced polyester.
- Weight: 39 kg
- No. doors: 2
- Colour: Grey Ral7035
- Fire Retardant: self-extinguishing 960 degrees test. Halogen free.
- Electromagnetic compatible: double insulation. No electrical contact risks.
- IEC62208:2011 certified
- Suitable for indoor or outdoor use
- Triple lock system for added security and maintaining IP rating
- 180 degrees door opening
- UV resistant, ideal for inclement weather conditions
- Easy to install in the ground with a pedestal, in concrete, on tarmac or attached to machinery

ENVIRONMENTAL PERFORMANCE

- Minimum temperature -30°C
- Maximum temperature +70°C
- Compression resistance 100 Kg
- IP43 weather protection
- Impact protection degree IK10

TRICEL CONSTRUCTION

* Approximate dimensions.
In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

TRICEL UK
Tel: +44 (0)1453 791616
Registered number 02868648

TRICEL IRL
Tel: +353 (0)64 663 2421
Registered number IE 075014

STOCK CODE:
103970

IP43 DOUBLE DOOR ELECTRICAL ENCLOSURE

750 x 1000 x 300MM

COMPLIES TO IEC 62208:2011

INDUSTRIAL ENCLOSURES BY TRICEL

40+ YEARS TECHNICAL EXPERIENCE

ELECTRICAL PERFORMANCE

- Nominal tension direct current up to 1500Vdc
- Nominal tension alternative current up to 1000Vac

INSTALLATION AND ASSEMBLY

- Inside installation
- Outdoor installation
- Floor mounting
- Plinth mounting
- Product supplied assembled

ASSOCIATED PRODUCTS



PLINTH (104034)
2 REQUIRED

TRICEL CONSTRUCTION

* Approximate dimensions.
In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

TRICEL UK
Tel: +44 (0)1453 791616
Registered number 02868648

TRICEL IRL
Tel: +353 (0)64 663 2421
Registered number IE 075014